

ITEM 502.82M REMOVE AND REPLACE JOINT SEALER AT CURB PROTECTION PLATES

DESCRIPTION

Under this item the CONTRACTOR shall remove, clean, and replace the existing joint sealer along the top of the entire length of the curb protection plate.

MATERIALS

The newly installed joint sealer material shall conform to all the provisions of NYSDOT Standard Specifications, Subsection 705-06 Caulking Compound for Structures, latest revision.

CONSTRUCTION DETAILS

Existing joint sealer should be removed, the CONTRACTOR taking care not to damage the curb protection plate or the concrete sidewalk. Any damage shall be repaired by the CONTRACTOR at no expense to the COUNTY. After removal, the CONTRACTOR shall sandblast the exposed surface free of any efflorescence, laitence, grease, or other foreign substances.

METHOD OF MEASUREMENT

The quantity to be paid for under this item will be the number of linear meters of joint sealer installed in accordance with the Plans and as directed by the ENGINEER.

BASIS OF PAYMENT

The unit price bid per linear meter shall include the cost of all labor, materials, and equipment necessary to complete the work.

Payment will be made under:

<u>Item No.</u>	<u>Item</u>	<u>Pay Unit</u>
502.82M	Remove and Replace Joint Sealer At Curb Protection Plates	M